



**600X600MM
MATT SERIES**

AMERICAN BASSWOOD



600 X 600 MM | GVT



MATT



ASH WOOD



600 X 600 MM | GVT

MATT



INDIAN ROSEWOOD



600 X 600 MM | GVT

MATT



MISTY BEIGE



600 X 600 MM | GVT

MATT



MISTY GREY



600 X 600 MM | GVT



MATT



OAK WOOD BEIGE



600 X 600 MM | GVT



MATT



OAK WOOD BRAWN



600 X 600 MM | GVT

MATT




SANDSTONE CREMA



600 X 600 MM | GVT

MATT



STONE BEIGE



600 X 600 MM | GVT



MATT



TEAKWOOD NATURAL



600 X 600 MM | GVT

MATT



TIMBER WOOD



600 X 600 MM | GVT



MATT



WALNUT CHERRY



600 X 600 MM | GVT

MATT



TECHNICAL SPECIFICATION

TEST DESCRIPTION	TEST METHOD	ISO STANDARD REFER TO IN TABLE	VALUE
 Tensile strength	ISO 224-02 10000.0	> 0.0%	> 0.0%
 Tensile strength	ISO 224-02 10000.0	> 0.0%	> 0.0%
 Tensile strength of joints	ISO 224-02 10000.0	> 0.0%	> 0.0%
 Tensile strength	ISO 224-02 10000.0	> 0.0%	> 0.0%
 Surface texture	ISO 224-02 10000.0	> 0.0%	> 0.0%
 Water absorption	ISO 224-02 10000.0	< 0.0%	< 0.0%
 Swelling shrinkage	ISO 224-02 10000.0	< 0.0%	< 0.0%
 Modulus of rupture	ISO 224-02 10000.0	< 0.0 MPa	< 0.0 MPa
 Modulus of rupture	ISO 224-02 10000.0	< 0.0 MPa	< 0.0 MPa
 Load thermal expansion	ISO 224-02 10000.0	1.5 x 10 ⁻³ °C	1.5 x 10 ⁻³ °C
 Flame spread	ISO 224-02 10000.0	No visible effect	No visible effect
 Flame spread	ISO 224-02 10000.0	No visible effect	No visible effect
 Resistance to abrasion	ISO 224-02 10000.0	No visible effect	No visible effect
 Resistance to abrasion	ISO 224-02 10000.0	No visible effect	No visible effect
 Color fastness	ISO 224-02 10000.0	No change	No change
 Color fastness in UV light	ISO 224-02	No change in color	No change in color
 Impact resistance (ASTM D256)	ISO 224-02	> 0.0000	> 0.0000
 Surface quality	ISO 224-02 10000.0	90% 80%	No visible effect
 Dimensional stability	ISO 224-02 10000.0	< 0.0	< 0.0
 Dimensional stability	ISO 224-02 10000.0	0	0

Note: * Values shown in the catalogue may vary with the original file. ** Weight shown is not suitable as an inherent property of material - without film.

Packing details

SIZE	NO. OF TILES	COVERAGE AREA
600 x 600 mm	4 Pcs. per Box	1.44 sq mtr. (Approx.)

- A beautiful floor is considered to help in the best use of interior decoration. We want any visitor who has this floor to experience the best of floor in ambient design.
- A good flooring not only is beautiful but also when it's ready for years to come, but there are subject to daily grind and rigorous of feet traffic and its stains, ink stains, grease stains, etc. over the floor of tiles will stain if not maintained. Fortunately the situation is not completely fatal.

Polished, Washed Tiles High Strength Joint free

